





XR 480 BWS

Model: PR-2493

RoHS | CE |  WDMX | 470W |  10m |  IP₂₀ | T_c150°C | T_a45°C | 

The new hybrid versatile 3-in-1 luminaire XR 480 BWS integrates three features(Beam, Wash, Spot) in a single unit. It has adopted PR patented technology, combines advanced OSRAM 470W lamp technology with superb optical system. XR 480 BWS can enhances any shows with its massive 2.3° to 50° zoom range.

3 in 1, OSRAM 470W




Fixed gobos



Rotating gobos(Ø15.9mm, image Ø12.5mm)



Scan with your Phone
to view more detail



22.2Kg
Size(mm)

Specifications

- Input Voltages
100-240V AC, 50/60Hz
- Power Consumption
680W@220V
- Light Source
OSRAM SIRIUS HRI 470W S(7,800K±300K, 1,500 hrs)
- Strobe
Double shutter blades, 0.3~25 F.P.S
- Dimmer
0-100% linear adjustment
- Colors
CMY linear color mixing with macros
1 Color wheel: 13 dichroic color filters(with CTO) plus open
Rainbow effect with bi-directional and variable speeds
Stepping/linear color changing
- Gobos
1 Fixed gobo wheel: 10 gobos plus open
Bi-directionally rotatable, and shakable effect at variable speeds
1 Rotating gobo wheel: 9 interchangeable gobos plus open
Bi-directionally rotatable, and shakable at variable speeds
- Prism
Two prisms(standard: 8-facet and 16-facet prisms)
Optional: 3-facet/16-facet liner prism or gradient prism
Bi-directional rotating at variable speeds
- Frost
One frost filter
- Diffuser
One independent diffuser(optional even beam mode)
- Focus
DMX linear focus
- Zoom
DMX linear zoom
- Head Movement
Pan 540°, tilt 270° with auto position correction
- Light Angle
Beam mode: 2.3°~10°
Spot mode: 5°~40°
Wash mode: 5°~50°
- Control
International DMX512, 5 pins(optional 3 pins) interface
Short mode 23 channels, standard mode 28 channels,
extended mode 33 channels
Self-test mode
- Other Functions
Adjustable pan & tilt speed
LCD display screen
Fixture and lamp hours display
Modular structure for easy maintenance
DMX512 wireless receiver
DMX512 wireless transmitter(optional)
- Physical
Housing: high temperature engineering plastic, IP20
Ambient temperature: maximum 45°C
- Weight
Net weight: 22.2Kg
- Packaging
Standard: carton 640x510x530(mm)
Optional: flight case 860x550x750(mm)
- Accessories
G clamp, 2 pcs
5 pins XLR connector, 1 set
Safety cord, 1 pc
Optional: Ω clamp, 2 pcs

