

TANGO Spot

Model: PR-6610

RoHS | CE | LED | 1.5m | IP65 | Tc:150°C | Ta:40°C




TANGO Spot is a new launched outdoor powerful spot fixture, equipped with 620W bright white LED source. With precise control, 8°~56° wide zoom and multi dynamic effects. It's ideal for urban buildings lighting, landscape lighting and other multi-scale of locations.

IP65, LED Spot, Wash Effect



Scan with your Phone
to view more detail

Rotating gobos(Ø37.5mm, image Ø26mm)



37.2Kg
Size(mm)

Specifications

- Input Voltages
100-240V AC, 50/60Hz
- Power Consumption
800W@230V
- Light Source
Atria 620W LED white(7,000K), 20,000 hrs
- Strobe
Electronic strobe, 0.3-25 F.P.S
- Dimmer
0-100% linear adjustment
- Colors
1 Color wheel: 6 dichroic color filters plus open
Half color effect, rainbow effect with bi-directional and variable speeds
Stepping/linear color changing
- CTO
0-100% linear CTO system
- Gobo
1 Rotating gobo wheel: 6 replaceable gobos plus open, glass and metal gobos can be fixed
Bi-directionally rotating, index, shaking at variable speed and bi-directional scrolling effect
- Prism
Two prisms(4-facet and 6-facet array prisms)
Optional: 3-facet, coloured prism, 4-facet gradient prism
Bi-directionally rotating at variable speed, indexable
- Effect
Dual effect wheel, independent bi-directional rotation at variable speeds
Shaking effect at variable speeds
- Iris
5-100% linear adjustment with macros
- Focus
DMX linear focus
- Zoom
DMX linear zoom
- Light Angle
8°~56°
- Control
International DMX512, 3 pins(optional 5 pins) interface
RDM control protocol
Short mode 18 channels, standard mode 21 channels, extended mode 23 channels
Master-slave mode, stand-alone mode, test mode
- Other Functions
Lamp and total hours displayed
Over temperature protection
Fast and convenient software upgrade via DMX512 interface
Input signal isolation
Modular structure for easy maintenance
DMX512 wireless receiver
DMX512 wireless transmitter(optional)
- Physical
Housing: high-intensity die-casting aluminum, IP65
Ambient working temperature: 40°C
- Weight
Net weight: 37.2kg
- Packaging
Standard: carton 760x690x770(mm)
Optional: flight case 650x402x836(mm)
- Accessories
G clamp, 2 pcs
Power cord, 1 pc
Safety cord, 2 pcs
Signal adapter cord, 2 pcs

