

# LS BAR 336

Model: PR-6811

RoHS | CE | LED |  $\approx 1.5\text{m}$  | IP66 |  $T_c 150^\circ\text{C}$  |  $T_a 45^\circ\text{C}$  | 

LS BAR 336 is a new launched exterior bar, rating IP66. It's equipped with 36 pcs of 3W LEDs(12G+12B+12A), provides countless color mixing effects and versatile solution, ideal for multi-scale outdoor stages, buildings, theme parks, etc.



IP66, LED wash



Architectural Lighting



Scan with your Phone  
to view more detail



6.2Kg  
Size(mm)

## Specifications

- Input Voltages  
100-240V AC, 50/60Hz
- Power Consumption  
118W@220V
- Light Source  
36x3W LEDs(12G+12B+12A), 50,000 hrs
- Strobe  
Electronic strobe, 0-25 F.P.S
- Dimmer  
0-100% linear adjustment
- Colors  
G/B/A(customizable)
- Light Angle  
45° , 25° (W)x80° (L), 30° (W)x65° (L), 35° (W)x80° (L), 45° (W)x75°(L),
- Control  
International DMX512, 5 pins interface  
GBA mode 7 channels, HSIC mode 7 channels,  
Master-slave mode, test mode  
RDM protocol
- Other Functions  
DMX512 port program update  
Software upgrade convenient and quick through DMX cable  
Over temperature protection
- Physical  
Housing: aluminum profile of high strength die casting  
aluminum alloy, IP66  
Ambient working temperature: -20°C~40°C
- Weight  
Net weight: 6.2kg

- Packaging  
Standard: carton 1105x550x460(mm)  
Optional: flight case
- Accessories  
N/A

