

CUBIX 600

Model: PR-6602

RoHS | CE | WDMX | LED | 10m | IP65 | T_c55°C | T_a45°C | 




Version: 20240524

Cubix 600 is a waterproof and highly performing fixture using 300W white LED engine as its light source with ingress protection up to IP65 for indoor and outdoor applications. It has 1 color wheel (7 colors+open), 1 rotating gobo wheel (6 gobos+ open), 1 metal effect wheel, 1 pc of 4-facet circular prism and others. With highly performing optical system and other functions, the images of the gobos are clear and with sharp edges and without any distortions and the fixture has plenty of effects.

TANGO 180 Spot, LED



rotating gobos



21.4Kg
Size(mm)

Specifications

- Input voltage
100V~240V AC, 50/60Hz
- Rate power consumption
400W@230V
Power factor PF>0.9
- Power
300W White LED, 1pc(8000K) , 20000hrs
- Colors
1pc color wheel(6colors+CTO+Open),
Half color, bi-directional rainbow effect with variable speeds
Stepping /linear color selection
- Dimmer
Linear Dimmer from 0-100%
- Strobe
Electronic Strobe 0-25FP.S. with pulse macors
- Prism
1pc 4-facet circular prism
- Effect wheel
1 fire effect wheel
(bi-directional rotation with variable speeds)
Fire gobo exchangeable
- Gobo
1pc of rotating gobo wheel:6 gobos +open
Shake with variable speeds, bi-directional scrolling with variable speeds
- Focus
DMX linear focus
- Zoom
DMX linear zoom
- Beam angle
Beam angle (1/2θpeak): linear focus 7°~ 45°(open hole)
- Frost
1frost filter
- Control
International standard DMX512 signal control protocol
DMX512 5pin interfaces
14channels in short mode and 19channels in standard mode
Master/Slave synchronized Mode
Stand alone mode, preset mode, user memory
- Other functions
Color touch screen and its brightness adjustable
DMX 512 port for firmware upgrade, a convenient and quick way for firmware upgrade via DMX cable
Over temperature protection
Fixture time, DMX512 channel value and software version will be displayed
Display can be inverted
Quick replacement of gobos
- Housing
Cast Aluminum , high temperature resistant/anti-UV ABS, IP65
- Net weight
21.4Kg
- Operation temperature
Maximum ambient temperature 45 °C
- Packaging
Standard: carton 700x690x480(mm)

Light Output

