


XR 380 BWS

Model: PR-2392A

RoHS | CE | DMX | 380W | 8m | IP20 | T_c80°C | T_a45°C | 

Version: 20220607

Moving Heads






3 in 1, 380W



Fixed gobos



Rotating gobos



19Kg
Size(mm)

Specifications

- Input voltage
200V~240V AC, 50/60Hz
- Power Consumption
500W@230V
Power factor PF>0.90
- Light Source
Lamp Philips MSD Silver 380W LL-2
Color temperature 7800K±300K
rated life 3000hrs
- Colors
3color wheel: 12colors+Open+CMY
- gobo wheel
1 fixed gobo wheel: 10 gobos+open
gobo diameter=6.5mm, its thickness=0.5mm
1 rotating gobo wheel: 7 gobos +open
Gobo diameter Ø12.5mm, 2.2mm thick
- Prism/Frost
1 8-facet prism and 1 16-facet prism
bi-directional rotation from slow to fast
- Focus
DMX linear focus
- Dimmer/Strobe
Strobe at variable speeds(15 F.P.S at maximum)
0-100% linear dimmer
- Head Movement
Pan 540°, Tilt 270° with 16 bit control
- Beam Angle
Beam mode 2°-20°
Spot mode 6°-30°
Wash mode 17°-45°

- Control
Projector and lamp information readable,
external DMX value received and thermal sensor built-in for
error and malfunction analysis
Preset memory
Unintentional head move to cause power-off, quiet fans for
cooling
International standard DMX 512 protocol, 5-pin interface
23channels in short mode and 28channels in standard
mode
- Optional Wirelss Control Module/RDM Module
Compliant with USITT DMX-512 (1986 and 1990) and
512-A Full DMX for fidelity and DMX framing integrity
Auto-detecting DMX framing size and speed
<5ms DMX delay
Frequency range 2402-2480 MHz
- Housing
High temperature ABS and aluminum , IP20
- Net Weight
19Kg
- Operation Temperature
Ambient temperature at maximum: 45°C
- Accessories
Safety cord, 1 pc
Power cord, 1 pc
Foldable clamp, 2 pcs

■ Light Output

