

# XR 380 BWS

Model: PR-2393A

RoHS | CE | WDMX | 8m | IP20 | T<sub>c</sub>80°C | T<sub>a</sub>40°C | 

Version: 20230321

Moving Heads






3 in 1



Fixed gobos



Rotating gobos



19Kg  
Size(mm)

## Specifications

- Input voltage  
200V~240V AC, 50/60Hz
- Power Consumption  
500W@230V  
Power factor PF>0.90
- Light Source  
Lamp MSD Platinum 300S Flex  
Color temperature 7800K±300K  
rated life 6000hrs
- Colors  
1color wheel: 11colors+ Open
- gobo wheel  
1 fixed gobo wheel: 10gobos+open  
gobo diameter=6.5mm, its thickness=0.5mm  
1 fire effect wheel  
1 rotating gobo wheel: 7 gobos +open  
Gobo diameter Φ12.5mm, 2.2mm thick
- Prism/Frost  
1 8-facet prism and 1 16-facet prism  
bi-directional rotation from slow to fast
- Focus  
DMX linear focus
- Dimmer/Strobe  
Strobe at variable speeds(15 F.P.S at maximum)  
0-100% linear dimmer
- Head Movement  
Pan 540°, Tilt 270° with 16 bit control
- Beam Angle  
Beam mode 2°-20°  
Spot mode 6°-30°  
Wash mode 17°-45°

- Control  
Projector and lamp information readable  
external DMX value received and thermal sensor built-in for error and malfunction analysis  
Preset memory  
Unintentional head move to cause power-off, quiet fans for cooling  
International standard DMX 512 protocol, 5-pin interface  
19channels in short mode and 23channels in standard mode
- Optional Wirelss Control Module/RDM Module  
Compliant with USITT DMX-512(1986 and 1990)and 512-A  
Full DMX for fidelity and DMX framing integrity  
Auto-detecting DMX framing size and speed  
<5ms DMX delay  
Frequency range 2402-2480 MHz
- Housing  
High temperature ABS and aluminum , IP20
- Net Weight  
19Kg
- Operation Temperature  
Ambient temperature at maximum: 40°C
- Accessories  
Safety cord, 1 pc  
clamp, 2 pcs  
Foldable clamp, 2 pcs  
User manual, 1 pc

## ■ Light Output

