

# AQUA XLED 6019

Model: PR-8229

RoHS | CE |  | WDMX |  5m |  IP<sub>65</sub> | T<sub>c</sub>75°C | 


Version: 20260528

AQUA XLED 6019 is with Beam and Wash modes. It has 19\*60W RGBW LEDs as its light engine, producing different lighting atmospheres with Zoom, rotating lens panel, pixel control, adjustable color temperature and color macros. Being water, dust and oil resistant, it's for all-weather applications like open-air stage performance, concert, dance hall and TV programs and helps a lot. It is not only a lighting product, but also an artwork which brings happiness and vitality.

LED, IP65



Moving Heads



23.5Kg   
Size(mm)

## Specifications

- Electric parameters
  - Voltage: AC100V-240V/50-60Hz
  - Power: 1350W
- Light source
  - Qty.: 19×60W RGBW LED high power imported LEDs
  - Rated life: 50000h
- Control
  - DMX512,RDM,Master/Slave mode
- DMX channel modes
  - 7 DMX channel modes
  - 21CH/26CH/35CH/43CH/78CH/92CH/97CH
- Pan and Tilt
  - Pan: 540°, Tilt:216°
- Optics
  - Highly precise and integrated PMMA lens and highly light transmitting quartz mixing rods
- Beam angle
  - 7°~45°, linear
- Beam effects
  - Stunning beam effect at small beam angles
- Wash effects
  - Even wash effect at medium and big beam angles
- Colors
  - Even RGBW color mixing without flickering ,fast rainbow effects
- Color temperature
  - 2500~10000K
- Macros
  - Macros for static and dynamic effects
- Strobe
  - 1-25Hz, electronic strobe and random strobes
- Dimmer
  - Electronic dimmer , 4 dimmer modes
- Zoom
  - Linear motorized zoom
- Lens rotation
  - Continual lens rotation with kaleidoscope and canton tower effects
- LED ring
  - Pixel control , dynamic marquee effects
- Screen
  - 1.77 inch OLED screen with Chinese/English menus
  - isolated signal system to avoid interference by external light and electronics and waterproof touch keys (password 1111 to unlock the screen)
- Smart control
  - Fixture' s and light source' s hours and its temperatures can be readable via menus
- Ingress protection
  - IP65, water, dust and dirt resistantfor yearly all-weather applications
- Net weight
  - 23.5KG